

CLAIM AMENDMENTS

Please amend the claims as follows:

1. (Currently Amended) A rigid screwed assembly for metal structures for forming the fastening of secondary sections (3) on an H-shaped receiving section (2) or the like, characterized in that there are incorporated in the areas of the assemblies comprising: U-shaped assembly accessories (1) which are arranged such that they are fitted between the side flanges and a web of the receiving section (2) to form the a fastening structure for of the secondary sections (3) by means of anchoring screws (4) which pass through ~~both the corresponding assembly parts of the receiving section, the secondary sections~~ sections (2 and 3) and the corresponding accessory or accessories (4).
2. (Currently Amended) A The rigid screwed assembly for metal structures according to claim 1 6, characterized in that wherein the U-shaped accessories (1) are U-shaped in their basic implementation with have a width corresponding to the a gap of the side flanges of the applied receiving section (2) and with a thickness that can vary varies according to the a degree of rigidity necessary in the U-shaped assemblies to be carried out.
3. (Currently Amended) A The rigid screwed assembly for metal structures according to claim 1 6, characterized in that wherein the U-shaped accessories having two side flanges and a web, the accessories (1) can have one or both of their side flanges of the

U-shaped accessories have with a greater length than that of than the side flanges of the applied receiving section (2) so as to form forming assemblies of secondary sections (3.2) directly on the a projecting part of the mentioned oversized side flanges with the greater length of said the U-shaped accessories (4) in the applied mounting.

4. (Currently Amended) ~~A~~ The rigid screwed assembly for metal structures according to claim 4, ~~characterized in that wherein the U-shaped accessories (1) can be provided with~~ have reinforcements (6) between ~~their~~ the side flanges and the web of the U-shaped accessories so as to increase the stiffness of ~~their formation.~~
5. (Currently Amended) ~~A~~ The rigid screwed assembly for metal structures according to claim 1, ~~characterized in that wherein the U-shaped accessories (1) can be~~ have closed ~~in their contour according to a prismatic tubular configuration (1.1),~~ including openings for accessing ~~the~~ an interior to facilitate handling ~~the~~ a fastening anchor.
6. (Currently Amended) A rigid screwed assembly for metal structures, comprising:
 - an H-shaped receiving section having side flanges and a web;
 - secondary sections having a front plate fixed at one end; and
 - U-shaped accessories arranged between the side flanges and the web of the receiving sections,

the receiving section, the secondary sections and the U-shaped accessories being coupled by means of screws passing through a plurality of aligned holes in the front plate of the secondary sections, the receiving section and the U-shaped accessories.